



Denison Mines Corp.
 Atrium on Bay, 595 Bay Street, Suite 402
 Toronto, ON M5G 2C2
 Ph. 416-979-1991 • Fx. 416-979-5893 • www.denisonmines.com

COMPLETE WHEELER RIVER DRILL RESULTS

(as of August 30, 2010)

Hole Number	Depth From (metres)	Depth To (metres)	Interval Thickness (metres)	Grade U ₃ O ₈ 0.05% cutoff	GT Grade X Thickness
WR-249	407.65	409	1.35	1.72	2.3
WR-251	386	388.25	2.25	0.77	1.7
WR-253	389	393.2	4.2	1.14	4.8
WR-258	397	402.5	5.5	11.82	65.0
WR-259	397	401.5	4.5	17.72	79.7
WR-260	395.7	397.2	1.5	0.25	0.4
WR-261	407.5	415	7.5	1.73	13.0
WR-266	414.5	415.5	1	3.76	3.8
WR-267	405	408.5	3.5	19.96	69.9
WR-268	409.5	414	4.5	9.26	41.7
WR-269*	407.75	409.25	1.5	9.09	13.6
WR-272	411	415.5	4.5	4.12	18.6
WR-273	405	411	6	62.61	375.6
WR-274	409.7	418	8.3	4.74	39.3
WR-276	422	424	2	1.57	3.1
WR-279	494	495	1	0.07	0.1
WR-281	405.5	407.5	2	2.08	4.2
WR-286	398.5	407.5	9	16.80	151.2
WR-287*	401.85	409.35	7.5	33.41	250.6
WR-290	403	408	5	8.02	40.1
WR-291A	392.5	395.5	3	10.35	31.0
WR-292	398	405.5	7.5	4.95	37.1
WR-293	417.5	419	1.5	0.51	0.8
WR-294*	397.55	399.25	1.7	10.46	17.8
WR-295*	391.65	392.55	0.9	2.90	2.6
WR-299	400.5	406	5.5	10.20	56.1
WR-300	407.5	411	3.5	31.46	110.1
WR-301	405	413.5	8.5	1.92	16.3
WR-302	406	414.5	8.5	9.09	77.2
WR-305	403	408	5	25.78	128.9
WR-306	406.5	414	7.5	33.22	249.2
WR-308	404.5	406.5	2	2.01	4.0
WR-311	402.5	409	6.5	6.66	43.3
WR-318	400.4	410.9	10.5	7.70	80.9
WR-325**	528.7	530.2	1.5	0.12	0.2
WR-327	401.5	409	7.5	1.96	14.7
WR-328*	374.4	375.2	0.8	9.65	7.7
WR-329**	397.05	400.2	3.15	0.23	0.7
WR-330	402.5	406.5	4	1.09	4.4

Hole Number	Depth From (metres)	Depth To (metres)	Interval Thickness (metres)	Grade U ₃ O ₈ 0.05% cutoff	GT Grade X Thickness
WR-332**	414.65	415.55	0.9	0.07	0.1
WR-333	397.4	399.9	2.5	34.80	87.0
WR-334	406.5	411	4.5	7.96	35.8
WR-335	402	404.5	2.5	4.91	12.3
WR-337**	411.65	413.85	2.2	0.13	0.3
WR-341A**	400.3	401.1	0.8	0.27	0.2
WR-342*	407.5	411.8	4.3	28.28	121.6
WR-343*	409.6	411.3	1.7	16.2	27.5
WR-344**	396.7	401.6	4.9	0.66	3.2
WR-345*	402.1	404.8	2.7	17.59	47.5
WR-346**	402.5	404.9	2.4	0.35	0.8
WR-347*	398.8	400.8	2	9.88	19.8
WR-348*	387.8	390.6	2.8	6.2	17.4
WR-349**	409.9	410.9	1	0.24	0.2
WR-351*	387.9	388.7	0.8	10.64	8.5
WR-353**	384.1	385.6	1.5	0.41	0.6
WR-354**	410.1	410.5	0.4	0.13	0.05

* eU₃O₈ 1% cutoff

** eU₃O₈ 0.05% cutoff